

INDUSTRIAL COMPONENT DATA

FUSE 315A 690V DIN 1 GR 170M4184 EATON ELECTRIC cartridge fuse, ultra rapid, 315 A, AC 690 V, 1 DIN, 52 x 66..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 690V DIN 1 GR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 690V DIN 1 GR
Catalog number	170M4184
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-93E0F0D011
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 315 A, AC 690 V, 1 DIN, 52 x 66 x 135 mm, gR, DIN, IEC, simple indicator

FUSE 315A 690V DIN 1 GR

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 315A, 200 kAIC, Top fuse status indicator, Fuse, Blade end X Din 43-620 blade end, Class gR, DIN 43 620

Fuse, Fuse-link, high speed, 315 A, AC 690 V, DIN 1, 52 x 66 x 135 mm, gR, DIN, IEC, single indicator, square body with knife blade contacts, live gripping lugs, indicator style T for microswitch, semiconductor protection, DIN 43620, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M4184 Model Code FUSE 315A 690V DIN 1 GR EAN 5027590451666 UPC 051712334358 Product Length/Depth 245 mm Product Height 62 mm Product Width 142 mm Product Weight 398 g Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 315 A Breaking capacity 200 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category gR (general purpose semiconductor protection) Voltage type AC Fuse size 1 Rated voltage AC 690 V Current type

AC Class Class gR Clearing (I2T) 135000 at 600 V Watt losses 41 W Fuse shape Square body, knife blade contacts Pre arc (I2T) 26000 Color None Interrupt rating 200 kAIC Fitted with: Type T Indicator for micro Connection Blade end x Din 43-620 blade end Construction size 1 Packaging type Standard Voltage rating 690 V (IEC) Fuse type DIN 43620

T indicator for micro

Bladed Fuse system (according to IEC 60269) Other

ETIM for 170M4184 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

315 A

Utilization category according to IEC 60269 (EF002572)

gR (general purpose....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 690V DIN 1 GR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.