

INDUSTRIAL COMPONENT DATA

FUSE 315A 690V DIN 2 GR 170M5883 EATON ELECTRIC cartridge fuse, ultra rapid, 315 A, AC 690 V, DIN 2, 60 x 74..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 315A 690V DIN 2 GR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 315A 690V DIN 2 GR
Catalog number	170M5883
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-77DF9E70F1
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 315 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, simple indicator

FUSE 315A 690V DIN 2 GR

Fuse-link, high speed, 315 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, single indicator

Fuse, Fuse-link, high speed, 315 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, single indicator, square body with knife blade contacts, live gripping lugs, indicator style T for microswitch, semiconductor protection, DIN 43620, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M5883 Model Code FUSE 315A 690V DIN 2 GR EAN 5027590461115 UPC 051712268165 Product Length/Depth 210 mm Product Height 80 mm Product Width 160 mm Product Weight 477 g Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Electrical data

Amperage Rating 315 A Voltage rating 690 V (IEC) Voltage type AC Clearing (I₂T) 105000 at 600 V Pre arc (I₂T) 19500 Watt losses 46 W Breaking capacity 200 kA Class Class gR Product specification

Fuse size 2 Fitted with: Type T Indicator for micro

ETIM for 170M5883 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

315 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

46 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 315A 690V DIN 2 GR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.