

INDUSTRIAL COMPONENT DATA

FUSE 32A 2000VDC 1C/A170 SST AR 170M2048 EATON

ELECTRIC Fuse-link, high speed, 32 A, DC 2000 V, 39 x 66 x 21..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 32A 2000VDC 1C/A170 SST AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 32A 2000VDC 1C/A170 SST AR
Catalog number	170M2048
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-5DB65CC25D
Generated	2026-08-05

Product Overview

Fuse-link, high speed, 32 A, DC 2000 V, 39 x 66 x 216 mm, aR, IEC, with indicator

FUSE 32A 2000VDC 1C/A170 SST AR

Fuse, Fuse-link, high speed, 32 A, DC 2000 V, 39 x 66 x 216 mm, aR, IEC, with indicator, square body with offset bolted tags, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 32 A, DC 2000 V, 39 x 66 x 216 mm, aR, IEC, with indicator Fuse, Fuse-link, high speed, 32 A, DC 2000 V, 39 x 66 x 216 mm, aR, IEC, with indicator, square body with offset bolted tags, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 100 kA [Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 32 A Rated voltage DC 2000 V

Size 39 x 66 x 216 mm Utilization category aR Status indicator with indicator Description indicator style K for microswitch

Breaking Capacity 100 kA usable for size/applications traction

third rail Standard/Approval IEC Shape square body with offset bolted tags Standards/Regulations IEC 60269-4]

ETIM for 170M2048 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
1
Type of current (EF000143)
DC
Rated voltage DC (EF012281)
2000 V
Rated current (EF000227)
32 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
100 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Other
Power loss at rated current (EF012389)
18 W
Mounting holes (EF021553)
M8
Centre-to-centre distance of connections (EF021151)
197 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 32A 2000VDC 1C/A170 SST AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.