

INDUSTRIAL COMPONENT DATA

FUSE 32A 750V DC 000FU/70 AR CU 170M1751 EATON
ELECTRIC Fuse-link, high speed, 32 A, DC 750 V, size 000, 24

□ □

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 32A 750V DC 000FU/70 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 32A 750V DC 000FU/70 AR CU
Catalog number	170M1751
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-F9E5850BAC
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 32 A, DC 750 V, size 000, 24 x 36 x 96 mm, aR, IEC, UL

FUSE 32A 750V DC 000FU/70 AR CU

Fuse, Fuse-link, high speed, 32 A, AC 690 V, size 000, 24 x 36 x 96 mm, aR, IEC, UL, square body with offset bolted tags, IGBT circuits, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Busmann Series High speed fuses**

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M1751 Model Code FUSE 32A 750V DC 000FU/70 AR CU EAN 5027590441476 UPC 051712324090 Product Length/Depth 101 mm Product Height 42 mm Product Width 140 mm Product Weight 142 g Compliances Not Applicable Certifications UL Recognized Electrical data Amperage Rating 32 A Voltage rating 750 V Voltage type AC Watt losses 13 W Breaking capacity 50 kA Class Class aR Product specification

Fuse size 000

ETIM for 170M1751 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
000
Type of current (EF000143)
DC
Rated voltage DC (EF012281)
750 V
Rated current (EF000227)
32 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
50 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
13 W
Mounting holes (EF021553)
M8
Centre-to-centre distance of connections (EF021151)
73.8 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 32A 750V DC 000FU/70 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.