

INDUSTRIAL COMPONENT DATA

170M3397 EATON ELECTRIC Fuse-link, high speed, 350 A, AC 1250 V, compact size 1, 45 x 59 x 75 mm, aR, IEC, U..

Brand: EATON - MOELLER | Manufacturer Part Number: 170M3397



Manufacturer	EATON - MOELLER
MPN / Reference	170M3397
Catalog number	10000
Category	HRC fuse
Minimum order	4 Pcs
Document ID	EO-75D61A5C9F
Generated	2026-08-06

Product Overview

FUSE 350A 1300V UL 1*BKN/75 AR CU

Fuse-link, high speed, 350 A, AC 1250 V, compact size 1, 45 x 59 x 75 mm, aR, IEC, UL, single indicator

Fuse, Fuse-link, high speed, 350 A, AC 1250 V, compact size 1, 45 x 59 x 75 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed square body fuse Catalog Number 170M3397 EAN 5027590447492
UPC 051712255943 Product Length/Depth 96 mm Product Height 50 mm Product Width 170 mm Product Weight 158.5 g
Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Electrical data

Amperage Rating 350 A Voltage rating 1250 V (IEC), 1300 V (UL) Voltage type AC/DC Clearing (I₂T) 165000 at 1000 V,
220000 at 1250 V Pre arc (I₂T) 27000 Watt losses 65 W Breaking capacity 100 kA Class Class aR Product specification

Fuse size 1* Fitted with: Type K Indicator for micro

ETIM for 170M3397 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

1250 V

Rated current (EF000227)

350 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Centre fuse status indicator

Power loss at rated current (EF012389)

65 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

74 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 170M3397 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.