

INDUSTRIAL COMPONENT DATA

FUSE 350A 1250V 2GKN/75 AR CU 170M5591 EATON

ELECTRIC Fuse-link, high speed, 350 A, AC 1250 V, size 2, 61 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 350A 1250V 2GKN/75 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 350A 1250V 2GKN/75 AR CU
Catalog number	170M5591
Category	HRC fuse
Minimum order	4 Pcs
Document ID	EO-9136E5C19F
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 350 A, AC 1250 V, size 2, 61 x 77 x 75 mm, aR, IEC, UL, single indicator

FUSE 350A 1250V 2GKN/75 AR CU

Fuse-link, high speed, 350 A, AC 1250 V, 100 kA, size 2, 61 x 77 x 75 mm, aR, IEC, UL, type K indicator, US thread

Fuse, Fuse-link, high speed, 350 A, AC 1250 V, size 2, 61 x 77 x 75 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 350 A, AC 1250 V, 100 kA, size 2, 61 x 77 x 75 mm, aR, IEC, UL, type K indicator, US thread

Fuse-link, high speed, 350 A, AC 1250 V, size 2, 61 x 77 x 75 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 350 A Rated voltage AC 1250

V Construction size size 2 Size 61 x 77 x 75 mm Utilization category aR Status indicator type K indicator Description US

thread Breaking Capacity 100 kA Usable for size/application semiconductor protection Standard/Approval IEC

UL Shapes square body with flush end contacts Standards/Regulations IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 350 A Rated voltage 1250 V Voltage type AC Rated switching capacity 100 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Other Insulated metal gripping lugs (IMGL) No

ETIM for 170M5591 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 350A 1250V 2GKN/75 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.