

INDUSTRIAL COMPONENT DATA

FUSE 350A 690V 00BTN/60 AR 170M2770 EATON ELECTRIC

Fuse-link, high speed, 350 A, AC 690 V, size 00, 30 x 62 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 350A 690V 00BTN/60 AR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 350A 690V 00BTN/60 AR
Catalog number	170M2770
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-C270CB5AAA
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 350 A, AC 690 V, size 00, 30 x 62 x 64 mm, aR, IEC, single indicator

FUSE 350A 690V 00BTN/60 AR

Fuse, Fuse-link, high speed, 350 A, AC 690 V, size 00, 30 x 62 x 64 mm, aR, IEC, single indicator, square body with flush end contacts, indicator style T for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M2770 EAN 5027590443500
UPC 051712254519 Product Length/Depth 75 mm Product Height 77 mm Product Width 163 mm Product Weight 228.2 g
Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 350 A
Breaking capacity 200 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization
category aR (accompanied semiconductor protection) Voltage type AC Fuse size 00 Rated voltage AC 690 V
Center-to-center distance of connections 64 mm Current type AC Mounting dimension M8 Class Class aR Clearing (I2T)
91500 at 660 V Watt losses 60 W Fuse shape Square body, flush end contacts Pre arc (I2T) 13500 Color None Interrupt
rating 200 kAIC Fitted with: Type T Indicator for micro Connection Blade end x blade end Construction size 00 Mounting

method DIN 43 620

Flush Packaging type Standard Voltage rating 690 V (IEC) Fuse type Flush end

00BTN/60 Type T indicator for micro Fuse system (according to IEC 60269) IEC 60269-4 flush end connections type A

ETIM for 170M2770 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

00

Type of current (EF000143)

AC

Rated volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 350A 690V 00BTN/60 AR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.