

INDUSTRIAL COMPONENT DATA

FUSE 350A 690V 1*/80 AR UC 170M3018 EATON ELECTRIC

Fuse-link, high speed, 350 A, AC 690 V, compact DIN 1, 45..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 350A 690V 1*/80 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 350A 690V 1*/80 AR UC
Catalog number	170M3018
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-267317BB16
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 350 A, AC 690 V, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator

FUSE 350A 690V 1*/80 AR UC

Fuse, Fuse-link, high speed, 350 A, AC 690 V, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 350 A, AC 690 V, 200 kA, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator
Fuse-link, high speed, 350 A, AC 690 V, compact DIN 1, 45 x 45 x 104 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA
Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_n 350 A Rated voltage AC 690 V Construction size compact DIN 1 Size 45 x 45 x 104 mm Utilization category aR Status indicator single indicator Breaking Capacity 200 kA Usable for size/applications semiconductor protection Standard/Approval DIN

IEC Shapes square body with centre-bolted tags (slotted) Standards/Regulations DIN 43653

IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 350 A Rated voltage 690 V Voltage type AC Rated switching capacity 200

kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorTop fuse status indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170M3018 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of cu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 350A 690V 1*/80 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.