

INDUSTRIAL COMPONENT DATA

FUSE 350A 690V 1*BKN/50 AR UC 170M3468 EATON

ELECTRIC Fuse-link, high speed, 350 A, AC 690 V, compact size 1..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 350A 690V 1*BKN/50 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 350A 690V 1*BKN/50 AR UC
Catalog number	170M3468
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-EC5BB0C2EF
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 350 A, AC 690 V, compact size 1, aR, IEC, UL, single indicator

FUSE 350A 690V 1*BKN/50 AR UC

Fuse, Fuse-link, high speed, 350 A, AC 690 V, compact size 1, aR, IEC, UL, single (top) indicator system, square-body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M3468 EAN 5027590448062
UPC 051712815147 Product Length/Depth 60 mm Product Height 50 mm Product Width 43 mm Product Weight 267 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Electrical data

Amperage Rating 350 A Voltage rating 690 V (IEC), 700 V (UL) Voltage type AC Clearing (I2T) 68500 at 660 V Pre arc (I2T) 40 Watt losses 55 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 1* Fitted with: Type K Indicator for micro

ETIM for 170M3468 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

350 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Centre fuse status indicator

Power loss at rated current (EF012389)

55 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

50 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 350A 690V 1*BKN/50 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.