

INDUSTRIAL COMPONENT DATA

FUSE 400A 1250V 2BKN/75 AR CU 170M5392 EATON

ELECTRIC Fuse-link, high speed, 400 A, AC 1250 V, size 2, 61 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 400A 1250V 2BKN/75 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 400A 1250V 2BKN/75 AR CU
Catalog number	170M5392
Category	HRC fuse
Minimum order	4 Pcs
Document ID	EO-0AD003D1C2
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, AC 1250 V, size 2, 61 x 75 x 77 mm, aR, IEC, UL, single indicator

FUSE 400A 1250V 2BKN/75 AR CU

Fuse, Fuse-link, high speed, 400 A, AC 1250 V, size 2, 61 x 75 x 77 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M5392 Model Code FUSE 400A 1250V 2BKN/75 AR CU EAN 5027590456838 UPC 051712816748 Product Length/Depth 168 mm Product Height 80 mm Product Width 124 mm Product Weight 743.5 g Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 400 A

Breaking capacity 100 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization

category aR (accompanied semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 1250 V

Center-to-center distance of connections 74.3 mm Current type AC Mounting dimension M10 Class Class aR Clearing (I2T)

140000 at 1000 V, 180000 at 1250 V Watt losses 85 W Fuse shape Square body, flush end contacts Pre arc (I2T) 23000
Color None Interrupt rating 100 kAIC Fitted with: Type K Indicator for micro Construction size 2 Mounting method Flush
Packaging type Standard Voltage rating 1250 V (IEC), 1300 V (UL) Fuse type Flush end
BKN/75 Type K Indicator for Micro Fuse system (according to IEC 60269) IEC 60269-4 flush end connections type A
ETIM for 170M5392 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

2

Type o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 400A 1250V 2BKN/75 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.