

INDUSTRIAL COMPONENT DATA

FUSE 400A 1250V 2GKN/75 AR CU 170M5592 EATON

ELECTRIC Fuse-link, high speed, 400 A, AC 1250 V, size 2, 61 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 400A 1250V 2GKN/75 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 400A 1250V 2GKN/75 AR CU
Catalog number	170M5592
Category	HRC fuse
Minimum order	4 Pcs
Document ID	EO-EA3AEE8A4A
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, AC 1250 V, size 2, 61 x 77 x 75 mm, aR, IEC, UL, single indicator

FUSE 400A 1250V 2GKN/75 AR CU

Fuse-link, high speed, 400 A, AC 1250 V, 100 kA, size 2, 61 x 77 x 75 mm, aR, IEC, UL, type K indicator, US thread

Fuse, Fuse-link, high speed, 400 A, AC 1250 V, size 2, 61 x 77 x 75 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 400 A, AC 1250 V, 100 kA, size 2, 61 x 77 x 75 mm, aR, IEC, UL, type K indicator, US thread

Fuse-link, high speed, 400 A, AC 1250 V, size 2, 61 x 77 x 75 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

Delivery program
Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I] 400 A
Rated voltage AC 1250 V
Construction size size 2
Size 61 x 77 x 75 mm
Utilization category aR
Status indicator type K indicator
Description US thread
Breaking Capacity 100 kA
Usable for size/application semiconductor protection
Standard/Approval IEC UL
Shapes square body with flush end contacts
Standards/Regulations IEC 60269-4
Technical data ETIM 7.0

Aparatos de protección y fusibles (EG000020) / Fusible para baja tensión tipo NH (EC000055) Tecnología electrónica, de automatización y de mando de procesos / Instalación eléctricas, equipo / Inserto de fusibles / Inserto de fusibles de baja tensión ( [AFZ800015]) Tamaño de construcción Otros Corriente nominal 400 Ampere Tensión nominal 1250 Volt Tipo de tensión CA Capacidad de conmutación nominal/poder de corte 100 kiloampere Categoría de uso aR (protección suplementaria de semiconductores) Tipo de indicador de estado de fusible Otros

ETIM for 170M5592 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 400A 1250V 2GKN/75 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.