

INDUSTRIAL COMPONENT DATA

FUSE 400A 1500V 3L PV PV-400A-3L-U-15 EATON ELECTRIC FUSE 400A 1500V 3L PV

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 400A 1500V 3L PV



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 400A 1500V 3L PV
Catalog number	PV-400A-3L-U-15
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-95EEDF04CA
Generated	2026-08-05

Product Overview

FUSE 400A 1500V 3L PV

Fuse-link, high speed, 400 A, DC 1500 V, 3L, 75 x 91 x 205 mm, gPV, IEC, UL, no indicator, blade connections

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General Specifications

Product Name Eaton Bussmann series photovoltaic fuses Catalog Number PV-400A-3L-U-15 Ean 5996516002636 Product Length/Depth 217 mm Product Height 82 mm Product Width 94 mm Product Weight 1852 g Compliances CE Marked RoHS Compliant Certifications IEC 60269

UL Listed

CSA Certified Product specifications

Type Bladed Application Photovoltaic systems, inverters ,Photovoltaic array combiners and disconnects Amperage Rating 400 A Accessories Recomend fuse holders- SD1XL-S (for 01 and 1XL), SD2XL-S (for 2XL), SD3L-S (for 3L) , Breaking capacity 100 kA Voltage type DC Utilization category gPV (photovoltaic protection) Fuse indicator Top fuse status indicator Rated switching capacity 100 kA Fuse size 3L Current type DC Rated voltage DC 1500 V Class Class gPV Watt losses 61 W Fuse shape Square body Pre arc (I2T) 296000 Total I2T 1060000 at 1500 V Colour White Interrupt rating 100 kAIC Connection Blade end x blade end Construction size 3L Material Ceramic body Voltage rating 1500 Vdc Fuse type PV-3L-U-15 Fitted with: Blade without bolt holes Suitable for SD3L-S-PV XL Fuse base Fuse system (according to IEC 60269) Other Rated switching capacity DC 100 kA

ETIM for PV-400A-3L-U-15 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

3L

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

1500 V

Rated current (EF000227)

400 A

Utilization cate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 400A 1500V 3L PV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.