

INDUSTRIAL COMPONENT DATA

FUSE 400A 690V 2BN/50 AR UC 170M5408 EATON ELECTRIC

Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 77 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 400A 690V 2BN/50 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 400A 690V 2BN/50 AR UC
Catalog number	170M5408
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-F93DF81A6C
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator, flush end, M10

FUSE 400A 690V 2BN/50 AR UC

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 400 A, 200 kAIC, Top fuse status indicator, Fuse, Class aR, Flush

Fuse, Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator, square body with flush end contacts, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M5408 EAN 5027590456982
UPC 051712261135 Product Length/Depth 168 mm Product Height 80 mm Product Width 124 mm Product Weight 308.5 g
Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Electrical data

Amperage Rating 400 A Voltage rating 690 V (IEC), 700 V (UL) Voltage type AC Clearing (I2T) 74000 at 660 V Pre arc (I2T) 11000 Watt losses 65 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 2

ETIM for 170M5408 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

400 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

65 W

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

50.4 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 400A 690V 2BN/50 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.