

INDUSTRIAL COMPONENT DATA

FUSE 400A 690V 2E/91 AR UC 170M5308 EATON ELECTRIC

Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 61 x..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 400A 690V 2E/91 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 400A 690V 2E/91 AR UC
Catalog number	170M5308
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-3F348FC21E
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 61 x 126 mm, aR, IEC, single indicator

FUSE 400A 690V 2E/91 AR UC

Fuse, Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 61 x 126 mm, aR, IEC, single indicator, square body with centre-bolted tags (slotted), french style, indicator style T for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M5308 EAN 5027590456609
UPC 051712260855 Product Length/Depth 210 mm Product Height 80 mm Product Width 160 mm Product Weight 657 g
Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 400 A

Breaking capacity 200 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 690 V

Center-to-center distance of connections 90.9 mm Current type AC Mounting dimension Other Class Class aR Clearing (I2T) 74000 at 660 V Watt losses 65 W Fuse shape Square body, slotted center bolted tags Pre arc (I2T) 11000 Color None

Interrupt rating 200 kAIC Fitted with: Type T Indicator for micro Construction size 2 Packaging type Standard Voltage rating 690 V Fuse type French style
E/Type indicator for micro
Bolted tag Fuse system (according to IEC 60269) Other
ETIM for 170M5308 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
2
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
690 V
Rated current (EF000227)
400 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 400A 690V 2E/91 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.