

INDUSTRIAL COMPONENT DATA

FUSE 400A 690V 2GKN/50 AR UC 170M5558 EATON

ELECTRIC Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 77..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 400A 690V 2GKN/50 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 400A 690V 2GKN/50 AR UC
Catalog number	170M5558
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-4E7B665DD3
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, type K indicator, flush end, 16 UNC
FUSE 400A 690V 2GKN/50 AR UC

Fuse, Fuse-link, high speed, 400 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M5558 EAN 5027590457651
UPC 051712792783 Product Length/Depth 168 mm Product Height 80 mm Product Width 124 mm Product Weight 560 g

Compliances CE

RoHS Compliant

EAC Certifications IEC 60269-4

UL Electrical data

Amperage Rating 400 A Voltage rating 690 V (IEC), 700 V (UL) Voltage type AC Clearing (I2T) 74000 at 660 V Pre arc (I2T) 11000 Watt losses 65 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 2 Fitted with: Type K Indicator for micro
ETIM for 170M5558 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
IEC 60269-4 flush end connections type A
Fuse construction type according to IEC 60269 (EF015865)
2
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
690 V
Rated current (EF000227)
400 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
200 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Centre fuse status indicator
Power loss at rated current (EF012389)
65 W
Mounting holes (EF021553)
M8
Centre-to-centre distance of connections (EF021151)
50.4 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 400A 690V 2GKN/50 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.