

INDUSTRIAL COMPONENT DATA

FUSE 40A 690V 000/80 GR UC 170M1363 EATON ELECTRIC

Fuse-link, high speed, 40 A, AC 690 V, DIN 000, 21 x 40 x..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 40A 690V 000/80 GR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 40A 690V 000/80 GR UC
Catalog number	170M1363
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-620ADFA4C4
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 40 A, AC 690 V, DIN 000, 21 x 40 x 100 mm, gR, DIN, IEC, single indicator

FUSE 40A 690V 000/80 GR UC

Fuse, Fuse-link, high speed, 40 A, AC 690 V, DIN 000, 21 x 40 x 100 mm, gR, DIN, IEC, single indicator, square body with offset bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M1363 Model Code FUSE 40A 690V 000/80 GR UC EAN 5027590332774 UPC 051712216647 Product Length/Depth 105 mm Product Height 46 mm

Product Width 300 mm Product Weight 137.1 g Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Electrical data

Amperage Rating 40 A Voltage rating 690 V (IEC), 700 V (UL) Voltage type AC Clearing (I2T) 460 at 660 V Pre arc (I2T) 69 Watt losses 12 W Breaking capacity 200 kA Class Class gR Product specification

Fuse size 000

ETIM for 170M1363 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
000
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
690 V
Rated current (EF000227)
40 A
Utilization category according to IEC 60269 (EF002572)
gR (general purpose semiconductor protection)
Breaking capacity (EF005617)
200 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Top fuse status indicator
Power loss at rated current (EF012389)
12 W
Mounting holes (EF021553)
M8
Centre-to-centre distance of connections (EF021151)
76.7 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 40A 690V 000/80 GR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.