

INDUSTRIAL COMPONENT DATA

FUSE 40A 690V 1*EK/76 AR UC 170M3358 EATON ELECTRIC

Fuse-link, high speed, 40 A, AC 690 V, compact size 1, 4..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 40A 690V 1*EK/76 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 40A 690V 1*EK/76 AR UC
Catalog number	170M3358
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-647E19CDDA
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 40 A, AC 690 V, compact size 1, 45 x 59 x 102 mm, aR, IEC, UL, single indicator

FUSE 40A 690V 1*EK/76 AR UC

Fuse, Fuse-link, high speed, 40 A, AC 690 V, compact size 1, 45 x 59 x 102 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags (slotted), french style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M3358 EAN 5027590447232
UPC 051712255714 Product Length/Depth 78 mm Product Height 123 mm Product Width 155 mm Product Weight 705 g
Compliances RoHS Compliant
EAC
CE Certifications IEC 60269-4
UL 248-13 Electrical data
Amperage Rating 40 A Voltage rating 690 V Voltage type AC Clearing (I2T) 270 at 660 V Pre arc (I2T) 40 Watt losses 9 W
Breaking capacity 200 kA Class Class aR Product specification
Fuse size 1* Fitted with: Type K Indicator for micro
ETIM for 170M3358 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Centre fuse status indicator

Power loss at rated current (EF012389)

9 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

76 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 40A 690V 1*EK/76 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.