

INDUSTRIAL COMPONENT DATA

FUSE 500A 690V 2BN/50 AR UC 170M5410 EATON ELECTRIC

Fuse-link, high speed, 500 A, AC 690 V, size 2, 61 x 77 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 500A 690V 2BN/50 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 500A 690V 2BN/50 AR UC
Catalog number	170M5410
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-0ABF30E130
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 500 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator, flush end, M10

FUSE 500A 690V 2BN/50 AR UC

Fuse, Fuse-link, high speed, 500 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator, square body with flush end contacts, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M5410 EAN 5027590457002
UPC 051712793001 Product Length/Depth 168 mm Product Height 80 mm Product Width 124 mm Product Weight 308.5 g
Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 500 A
Breaking capacity 200 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization
category aR (accompanied semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 690 V
Center-to-center distance of connections 50.4 mm Current type AC Mounting dimension M10 Class Class aR Clearing (I2T)
145000 at 660 V Watt losses 75 W Fuse shape Square body, flush end contacts Pre arc (I2T) 21500 Color None Interrupt
rating 200 kAIC Construction size 2 Mounting method Flush Packaging type Standard Voltage rating 690 V (IEC), 700 V

(UL) Fuse type Flush end

B/Visual indicator Fuse system (according to IEC 60269) IEC 60269-4 flush end connections type A

ETIM for 170M5410 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

500 A

Utilization category according t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 500A 690V 2BN/50 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.