

INDUSTRIAL COMPONENT DATA

FUSE 50A 1250V 1*BKN/75 AR CU 170M3388 EATON

ELECTRIC Fuse-link, high speed, 50 A, AC 1250 V, compact size 1..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 50A 1250V 1*BKN/75 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 50A 1250V 1*BKN/75 AR CU
Catalog number	170M3388
Category	HRC fuse
Minimum order	4 Pcs
Document ID	EO-1BE401BB89
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 50 A, AC 1250 V, compact size 1, 45 x 59 x 75 mm, aR, IEC, UL, single indicator

FUSE 50A 1250V 1*BKN/75 AR CU

Fuse, Fuse-link, high speed, 50 A, AC 1250 V, compact size 1, 45 x 59 x 75 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 50 A, AC 1250 V, 100 kA, compact size 1, 45 x 59 x 75 mm, aR, IEC, UL, type K indicator
Fuse-link, high speed, 50 A, AC 1250 V, compact size 1, 45 x 59 x 75 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 50 A
Rated voltage AC 1250 V
Construction size compact size 1
Size 45 x 59 x 75 mm
Utilization category aR
Status indicator type K indicator
Breaking Capacity 100 kA
Usable for size/application semiconductor protection
Standard/Approval IEC

UL Shapes square body with flush end contacts
Standards/Regulations IEC 60269-4
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current50 ARated voltage1250 VVoltage typeACRated switching capacity100 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorOtherInsulated metal gripping lugs (IMGL)No

ETIM for 170M3388 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

Other

Type...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 50A 1250V 1*BKN/75 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.