

INDUSTRIAL COMPONENT DATA

FUSE 550A 690V 1*FKE/115 AR UC 170M3772 EATON

ELECTRIC Fuse-link, high speed, 550 A, AC 690 V, compact size ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 550A 690V 1*FKE/115 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 550A 690V 1*FKE/115 AR UC
Catalog number	170M3772
Category	HRC fuse
Minimum order	2 Pcs
Document ID	EO-1D976CD1EF
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 550 A, AC 690 V, compact size 1, 45 x 59 x 148 mm, aR, IEC, UL, single indicator

FUSE 550A 690V 1*FKE/115 AR UC

Fuse, Fuse-link, high speed, 550 A, AC 690 V, compact size 1, 45 x 59 x 148 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags, US style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed square body fuse Catalog Number 170M3772 EAN 5027590450034
UPC 051712257299 Product Length/Depth 92 mm Product Height 60 mm Product Width 163 mm Product Weight 176 g
Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 550 A
Breaking capacity 200 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 1* Rated voltage AC 690 V

Center-to-center distance of connections 117 mm Current type AC Mounting dimension M10 Class Class aR Clearing (I2T) 230000 at 660 V Watt losses 75 W Fuse shape Square body, center bolted tags Pre arc (I2T) 34000 Color None Interrupt rating 200 kAIC Fitted with: Type K Indicator for micro Connection Blade end x blade end Construction size Other Packaging type Standard Voltage rating 690 V Fuse type US Style FKE/115 Type K indicator for micro Bolted tag Fuse system (according to IEC 60269) Other ETIM for 170M3772 Circuit breakers and fuses (EC004556) Feature Name Feature Value Fuse system according to IEC 60269 (EF017676) Other Fuse construction type according to IEC 60269 (EF015865) Other Type of current (EF000143) AC Rated voltage AC (EF007682) 690 V Rated current (EF000227) 550 A Utilization category according to I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 550A 690V 1*FKE/115 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.