

INDUSTRIAL COMPONENT DATA

FUSE 630A 690V 1*BKN/50 AR UC 170M3473 EATON

ELECTRIC Fuse-link, high speed, 630 A, AC 690 V, compact size 1..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 630A 690V 1*BKN/50 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 630A 690V 1*BKN/50 AR UC
Catalog number	170M3473
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-CD79D10B12
Generated	2026-08-04

Product Overview

Fuse-link, high speed, 630 A, AC 690 V, compact size 1, aR, IEC, UL, single indicator

FUSE 630A 690V 1*BKN/50 AR UC

Fuse, Fuse-link, high speed, 630 A, AC 690 V, compact size 1, aR, IEC, UL, single (top) indicator system, square-body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M3473 EAN 5027590448284

UPC 051712217200 Product Length/Depth 60 mm Product Height 50 mm Product Width 43 mm Product Weight 263 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 630 A

Breaking capacity 200 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization

category aR (accompanied semiconductor protection) Voltage type AC Fuse size 1* Rated voltage AC 690 V

Center-to-center distance of connections 50 mm Current type AC Mounting dimension M8 Class Class aR Clearing (I2T)

325000 at 660 V Watt losses 80 W Fuse shape Square body, flush end contacts Pre arc (I2T) 48500 Color None Interrupt rating 200 kAIC Fitted with: Type K Indicator for micro Construction size Other Mounting method Flush Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type Flush end BKN/Type K Indicator for Micro Fuse system (according to IEC 60269) IEC 60269-4 flush end connections type A ETIM for 170M3473 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 630A 690V 1*BKN/50 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.