

INDUSTRIAL COMPONENT DATA

FUSE 630A 690V 1*KN/80 AR UC 170M3123 EATON ELECTRIC
Fuse-link, high speed, 630 A, AC 690 V, compact DIN 1, ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 630A 690V 1*KN/80 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 630A 690V 1*KN/80 AR UC
Catalog number	170M3123
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-DC79D74BB7
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 630 A, AC 690 V, compact DIN 1, 45 x 59 x 104 mm, aR, DIN, IEC, single indicator

FUSE 630A 690V 1*KN/80 AR UC

Fuse, Fuse-link, high speed, 630 A, AC 690 V, compact DIN 1, 45 x 59 x 104 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style K for microswitch, semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFO for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Busmann Series High speed fuses**

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M3123 EAN 5027590444033

UPC 051712254922 Product Length/Depth 290 mm Product Height 62 mm Product Width 142 mm Product Weight 319 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 630 A

Breaking capacity 200 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization

category aR (accompanied semiconductor protection) Voltage type AC Fuse size 1* Rated voltage AC 690 V

Center-to-center distance of connections 76.4 mm Current type AC Mounting dimension M10 Class Class aR Clearing (I2T)

325000 at 660 V Watt losses 80 W Clearing loss 80 Fuse shape Square body, slotted center bolted tags Pre arc (I2T)

48500 Color None Interrupt rating 200 kAIC Connection Blade end x blade end Construction size Other Mounting method
DIN 43 620 Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type DIN 43653
KN/80 Type K Indicator for Micro
Bolted tag Fuse system (according to IEC 60269) Other
ETIM for 170M3123 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
690 V
Rated current (EF000227)
630 A
Util...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 630A 690V 1*KN/80 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.