

INDUSTRIAL COMPONENT DATA

FUSE 630A 690V DIN 2 GR 170M5889 EATON ELECTRIC cartridge fuse, ultra rapid, 630 A, AC 690 V, DIN 2, 60 x 74..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 630A 690V DIN 2 GR



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 630A 690V DIN 2 GR
Catalog number	170M5889
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-E5AF1D81BF
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 630 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, simple indicator

FUSE 630A 690V DIN 2 GR

Fuse-link, 630 A, AC 690 V, 200 kA, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, type T indicator, live gripping lugs

Fuse, Fuse-link, high speed, 630 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, single indicator, square body with knife blade contacts, live gripping lugs, indicator style T for microswitch, semiconductor protection, DIN 43620, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, 630 A, AC 690 V, 200 kA, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, type T indicator, live gripping lugs
Fuse-link, high speed, 630 A, AC 690 V, DIN 2, 60 x 74 x 150 mm, gR, DIN, IEC, single indicator, square body with knife blade contacts, live gripping lugs, indicator style T for microswitch, semiconductor protection, DIN 43620, IEC 60269-4, Breaking Capacity 200 kA
Delivery program

Product range FuseBasic function Fuse-linkRated current [I]_n630 ARated voltageAC 690 VConstruction sizeDIN 2Size60 x 74 x 150 mmUtilization categorygRStatus indicator type T indicatorDescriptionlive gripping lugsBreaking Capacity200 kAusable for size/applicationssemiconductor protectionStandard/ApprovalDIN

IECShapesquare body with knife blade contactsStandards/RegulationsDIN 43620

IEC 60269-4Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current630 ARated voltage690 VVoltage typeACRated switching capacity200
kAUtilization categorygR (general purpose semiconductor protection)Type of fuse status indicatorTop fuse status
indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170M5889 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 630A 690V DIN 2 GR with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.