

INDUSTRIAL COMPONENT DATA

FUSE HI SPEED SEMICOND. TYPE 170M5747 EATON

ELECTRIC Fuse-link, high speed, 700 A, AC 1100 V, size 2, 61 x 7..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE HI SPEED SEMICOND. TYPE



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE HI SPEED SEMICOND. TYPE
Catalog number	170M5747
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-B514AC7619
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 700 A, AC 1100 V, size 2, 61 x 77 x 160 mm, aR, IEC, UL, single indicator

FUSE 700A 1100V 2FKE/115 AR

Fuse-link, high speed, 700 A, AC 1100 V, 100 kA, size 2, 61 x 77 x 160 mm, aR, IEC, UL, type K indicator, US style

Fuse, Fuse-link, high speed, 700 A, AC 1100 V, size 2, 61 x 77 x 160 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags, US style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 700 A, AC 1100 V, 100 kA, size 2, 61 x 77 x 160 mm, aR, IEC, UL, type K indicator, US style
Fuse-link, high speed, 700 A, AC 1100 V, size 2, 61 x 77 x 160 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags, US style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I] 700 A
Rated voltage AC 1100 V
Construction size size 2
Size 61 x 77 x 160 mm
Utilization category aR
Status indicator type K indicator
Description US style
Breaking Capacity 100 kA
Usable for size/application semiconductor protection
Standard/Approval IEC UL
Shapes square body with centre-bolted tags
Standards/Regulations IEC 60269-4
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 700 A Rated voltage 1100 V Voltage type AC Rated switching capacity 100 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator Other Insulated metal gripping lugs (IMGL) No
ETIM for 170M5747 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
2
Type of current (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE HI SPEED SEMICOND. TYPE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.