

INDUSTRIAL COMPONENT DATA

FUSE 700A 1250V 2TN/110 AR CU 170M5197 EATON

ELECTRIC Fuse-link, high speed, 700 A, AC 1250 V, size 2, 61 X ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 700A 1250V 2TN/110 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 700A 1250V 2TN/110 AR CU
Catalog number	170M5197
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-5EE24F7EE9
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 700 A, AC 1250 V, size 2, 61 x 75 x 138 mm, aR, DIN, IEC, type T indicator

FUSE 700A 1250V 2TN/110 AR CU

Fuse, Fuse-link, high speed, 700 A, AC 1250 V, size 2, 61 x 75 x 138 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), indicator style T for microswitch, semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M5197 Model Code FUSE 700A 1250V 2TN/110 AR CU EAN 5027590456142 UPC 051712260473 Product Length/Depth 284 mm Product Height 67 mm

Product Width 175 mm Product Weight 634 g Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Electrical data

Amperage Rating 700 A Voltage rating 1250 V (IEC), 1300 V (UL) Voltage type AC Clearing (I2T) 795000 at 1000 V, 1050000 at 1250 V Pre arc (I2T) 160000 Watt losses 115 W Breaking capacity 100 kA Class Class aR Product specification Fuse size 2

ETIM for 170M5197 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

1250 V

Rated current (EF000227)

700 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Top fuse status indicator

Power loss at rated current (EF012389)

115 W

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

108 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 700A 1250V 2TN/110 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.