

INDUSTRIAL COMPONENT DATA

FUSE 700A 1250V 3BKN/80 AR CU 170M6545 EATON
ELECTRIC Fuse-link, high speed, 700 A, AC 1250 V, size 3, 76
X ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 700A 1250V 3BKN/80 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 700A 1250V 3BKN/80 AR CU
Catalog number	170M6545
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-90957DC8C4
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 700 A, AC 1250 V, size 3, 76 x 92 x 83 mm, aR, IEC, UL, single indicator

FUSE 700A 1250V 3BKN/80 AR CU

Fuse, Fuse-link, high speed, 700 A, AC 1250 V, size 3, 76 x 92 x 83 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Busmann Series High speed fuses**

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M6545 EAN 5996516019757
UPC 051712264495 Product Length/Depth 168 mm Product Height 76 mm Product Width 95 mm Product Weight 1308 g
Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Electrical data

Amperage Rating 700 A Voltage rating 1250 V (IEC), 1300 V (UL) Voltage type AC/DC Clearing (I2T) 705000 at 1000 V, 940000 at 1250 V Pre arc (I2T) 115000 Watt losses 120 W Breaking capacity 100 kA Class Class aR Product specification

Fuse size 3 Fitted with: Type K Indicator for micro

ETIM for 170M6545 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type A

Fuse construction type according to IEC 60269 (EF015865)

3

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

1250 V

Rated current (EF000227)

700 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

Centre fuse status indicator

Power loss at rated current (EF012389)

120 W

Mounting holes (EF021553)

M12

Centre-to-centre distance of connections (EF021151)

82.4 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 700A 1250V 3BKN/80 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.