INDUSTRIAL COMPONENT DATA

FUSE 700A 1250V 3GKN/75 AR CU 170M6595 EATON ELECTRIC Fuse-link, high speed, 700 A, AC 1250 V, size 3, 76 x ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 700A 1250V 3GKN/75 AR CU



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 700A 1250V 3GKN/75 AR CU
Catalog number	170M6595
Category	HRC fuse
Minimum order	2 Pcs
Document ID	EO-664CE9BFDE
Generated	2026-11-19

Product Overview

Fuse-link, high speed, 700 A, AC 1250 V, size 3, 76 x 92 x 76 mm, aR, IEC, UL, type K indicator, flush end, 13 UNC
FUSE 700A 1250V 3GKN/75 AR CU
Fuse-link, high speed, 700 A, AC 1250 V, 100 kA, size 3, 76 x 92 x 76 mm, aR, IEC, UL, square body with flush end contacts
Fuse, Fuse-link, high speed, 700 A, AC 1250 V, size 3, 76 x 92 x 76 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 700 A, AC 1250 V, 100 kA, size 3, 76 x 92 x 76 mm, aR, IEC, UL, square body with flush end contactsFuse, Fuse-link, high speed, 700 A, AC 1250 V, size 3, 76 x 92 x 76 mm, aR, IEC, UL, single indicator, square body with flush end contacts, indicator style K for microswitch, US thread, semiconductor protection, IEC 60269-4, Breaking Capacity 100 kADelivery program
Product rangeFuseBasic functionFuse-linkField of applicationhigh speedRated current [I]700 ARated voltageAC 1250 VConstruction sizesize 3Size76 x 92 x 76 mmUtilization categoryaRStatus indicatortype K indicatorDescriptionUS threadBreaking Capacity100 kAusable for size/applicationssemiconductor protectionStandard/ApprovalIEC

ULShapesquare body with flush end contactsStandards/RegulationsIEC 60269-4Technical data ETIM 7.0 Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015])Construction sizeOtherRated current700 ARated voltage1250 VVoltage typeACRated switching capacity100 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorOtherInsulated metal gripping lugs (IMGL)No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 700A 1250V 3GKN/75 AR CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.