

INDUSTRIAL COMPONENT DATA

FUSE 700A 690V 1/80 AR UC 170M4017 EATON ELECTRIC

Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 53 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 700A 690V 1/80 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 700A 690V 1/80 AR UC
Catalog number	170M4017
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-D4DDE2389A
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 53 x 108 mm, aR, DIN, IEC, single indicator

FUSE 700A 690V 1/80 AR UC

Fuse, Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 53 x 108 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 700 A, AC 690 V, 200 kA, DIN 1, 53 x 53 x 108 mm, aR, DIN, IEC, single indicator
Fuse, Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 53 x 108 mm, aR, DIN, IEC, single indicator, square body with centre-bolted tags (slotted), semiconductor protection, DIN 43653, IEC 60269-4, Breaking Capacity 200 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]
700 A
Rated voltage AC 690 V
Construction size DIN 1
Size 53 x 53 x 108 mm
Utilization category aR
Status indicators single indicator
Breaking Capacity 200 kA
Usable for size/application semiconductor protection
Standard/Approval DIN

IEC
Shapes square body with centre-bolted tags (slotted)
Standards/Regulations DIN 43653

IEC 60269-4
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])
Construction size Other
Rated current 700 A
Rated voltage 690 V
Voltage type AC
Rated switching capacity 200 kA
Utilization category aR (accompanied semiconductor protection)
Type of fuse status indicator Top fuse status

indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 170M4017 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
1
Type of current (EF000143)
AC
Rated vo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 700A 690V 1/80 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.