

INDUSTRIAL COMPONENT DATA

FUSE 700A 690V 3FKE/115 AR UC 170M6761 EATON

ELECTRIC Fuse-link, high speed, 700 A, AC 690 V, size 3, 76 x 9..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 700A 690V 3FKE/115 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 700A 690V 3FKE/115 AR UC
Catalog number	170M6761
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-F3F388B909
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 700 A, AC 690 V, size 3, 76 x 92 x 139 mm, aR, IEC, UL, single indicator

FUSE 700A 690V 3FKE/115 AR UC

Fuse, Fuse-link, high speed, 700 A, AC 690 V, size 3, 76 x 92 x 139 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags, US style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M6761 EAN 5996516020678
UPC 051712265522 Product Length/Depth 168 mm Product Height 76 mm Product Width 95 mm Product Weight 986 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Product specifications

Type Fuse Application semiconductor protection Amperage Rating 700 A Breaking capacity 200 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 3 Rated voltage AC 690 V Center-to-center distance of connections 114 mm Current

type AC Mounting dimension Other Class Class aR Clearing (I2T) 300000 at 660 V Watt losses 110 W Fuse shape Square body, center bolted tags Pre arc (I2T) 44500 Color None Interrupt rating 200 kAIC Fitted with: Type K Indicator for micro Connection Blade end x blade end Construction size 3 Packaging type Standard Voltage rating 690 V Fuse type US Style FKE/115 Type K indicator for micro

Bolted tag Fuse system (according to IEC 60269) Other
ETIM for 170M6761 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

3

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

700 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 700A 690V 3FKE/115 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.