

INDUSTRIAL COMPONENT DATA

FUSE 700A 690V 3FU/115 AR UC 170M6711 EATON ELECTRIC Fuse-link, high speed, 700 A, AC 690 V, size 3, 67 x 92..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 700A 690V 3FU/115 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 700A 690V 3FU/115 AR UC
Catalog number	170M6711
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-82A5CE98E7
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 700 A, AC 690 V, size 3, 67 x 92 x 155 mm, aR, IEC, UL

FUSE 700A 690V 3FU/115 AR UC

Fuse-link, high speed, 700 A, AC 690 V, 200 kA, size 3, 67 x 92 x 155 mm, aR, IEC, UL, US style

Fuse, Fuse-link, high speed, 700 A, AC 690 V, size 3, 67 x 92 x 155 mm, aR, IEC, UL, square body with centre-bolted tags, US style, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

Fuse-link, high speed, 700 A, AC 690 V, 200 kA, size 3, 67 x 92 x 155 mm, aR, IEC, UL, US style

Fuse, Fuse-link, high speed, 700 A, AC 690 V, size 3, 67 x 92 x 155 mm, aR, IEC, UL, square body with centre-bolted tags, US style,

semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]² 700 A Rated voltage AC 690

V Construction size size 3 Size 67 x 92 x 155 mm Utilization category aR Description US style Breaking Capacity 200 kA

Usable for size/application semiconductor protection Standard/Approval IEC

UL Shapes square body with centre-bolted tags Standards/Regulations IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 700 A Rated voltage 690 V Voltage type AC Rated switching capacity 200

kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator None Insulated metal gripping

lugs (IMGL)No

ETIM for 170M6711 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

3

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

690 V

Rated current (EF000227)

700 A

Utilization category according to....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 700A 690V 3FU/115 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.