

INDUSTRIAL COMPONENT DATA

FUSE 800A 690V 2BN/50 AR UC 170M5414 EATON ELECTRIC

Fuse-link, high speed, 800 A, AC 690 V, size 2, 61 x 77 ..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 800A 690V 2BN/50 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 800A 690V 2BN/50 AR UC
Catalog number	170M5414
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-F7DC2F270A
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 800 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator, flush end, M10

FUSE 800A 690V 2BN/50 AR UC

Fuse, Fuse-link, high speed, 800 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator, square body with flush end contacts, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M5414 Model Code FUSE 800A 690V 2BN/50 AR UC EAN 5027590457057 UPC 051712261197 Product Length/Depth 168 mm Product Height 80 mm

Product Width 124 mm Product Weight 297 g Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Electrical data

Amperage Rating 800 A Voltage rating 690 V (IEC), 700 V (UL) Voltage type AC Clearing (I2T) 575000 at 660 V Pre arc (I2T) 86000 Watt losses 105 W Breaking capacity 200 kA Class Class aR Product specification

Fuse size 2

ETIM for 170M5414 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
IEC 60269-4 flush end connections type A
Fuse construction type according to IEC 60269 (EF015865)
2
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
690 V
Rated current (EF000227)
800 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
200 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
Top fuse status indicator
Power loss at rated current (EF012389)
105 W
Mounting holes (EF021553)
M10
Centre-to-centre distance of connections (EF021151)
50.4 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 800A 690V 2BN/50 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.