

INDUSTRIAL COMPONENT DATA

FUSE 800A 690V 3FKE/90 AR UC 170M6662 EATON ELECTRIC

Fuse-link, high speed, 800 A, AC 690 V, size 3, 76 x 92..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 800A 690V 3FKE/90 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 800A 690V 3FKE/90 AR UC
Catalog number	170M6662
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-CF84160918
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 800 A, AC 690 V, size 3, 76 x 92 x 135 mm, aR, IEC, UL, single indicator

FUSE 800A 690V 3FKE/90 AR UC

Fuse-link, high speed, 800 A, AC 690 V, 200 kA, size 3, 76 x 92 x 135 mm, aR, IEC, UL, type K indicator, US style

Fuse, Fuse-link, high speed, 800 A, AC 690 V, size 3, 76 x 92 x 135 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags, US style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 800 A, AC 690 V, 200 kA, size 3, 76 x 92 x 135 mm, aR, IEC, UL, type K indicator, US style Fuse,
Fuse-link, high speed, 800 A, AC 690 V, size 3, 76 x 92 x 135 mm, aR, IEC, UL, single indicator, square body with
centre-bolted tags, US style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity
200 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_N 800 A Rated voltage AC 690
V Construction size size 3 Size 76 x 92 x 135 mm Utilization category aR Status indicator type K indicator Description US
style Breaking Capacity 200 kA Usable for size/application semiconductor protection Standard/Approval IEC
UL Shapes square body with centre-bolted tags Standards/Regulations IEC 60269-4 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process
control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current800 ARated voltage690 VVoltage typeACRated switching capacity200 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorOtherInsulated metal gripping lugs (IMGL)No

ETIM for 170M6662 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

3

Type of current (EF000143...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 800A 690V 3FKE/90 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.