

INDUSTRIAL COMPONENT DATA

FUSE 80A 690V 1*EK/76 AR UC 170M3361 EATON ELECTRIC

Fuse-link, high speed, 80 A, AC 690 V, compact size 1, 4..

Brand: EATON - MOELLER | Manufacturer Part Number: FUSE 80A 690V 1*EK/76 AR UC



Manufacturer	EATON - MOELLER
MPN / Reference	FUSE 80A 690V 1*EK/76 AR UC
Catalog number	170M3361
Category	HRC fuse
Minimum order	3 Pcs
Document ID	EO-835B1CFF52
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 80 A, AC 690 V, compact size 1, 45 x 59 x 102 mm, aR, IEC, UL, single indicator

FUSE 80A 690V 1*EK/76 AR UC

Fuse, Fuse-link, high speed, 80 A, AC 690 V, compact size 1, 45 x 59 x 102 mm, aR, IEC, UL, single indicator, square body with centre-bolted tags (slotted), french style, indicator style K for microswitch, semiconductor protection, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M3361 EAN 5027590447263
UPC 051712255745 Product Length/Depth 168 mm Product Height 80 mm Product Width 124 mm Product Weight 705 g
Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 80 A
Breaking capacity 200 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 1* Rated voltage AC 690 V
Center-to-center distance of connections 76 mm Current type AC Mounting dimension M8 Class Class aR Clearing (I2T) 1250 at 660 V Watt losses 18 W Fuse shape Square body, slotted center bolted tags Pre arc (I2T) 185 Color None Interrupt

rating 200 kAIC Fitted with: Type K Indicator for micro Construction size Other Packaging type Standard Voltage rating 690 V Fuse type French style
EKN/Type K Indicator for Micro
Bolted tag Fuse system (according to IEC 60269) Other
ETIM for 170M3361 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
690 V
Rated current (EF000227)
80 A
Utilization category according to IEC 60269 (EF002572)
aR (accompan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FUSE 80A 690V 1*EK/76 AR UC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.