

INDUSTRIAL COMPONENT DATA

S33-1/C/FORMP 027446 Y7-27446 EATON ELECTRIC Fuse base, 63A, 690 V, DIII/E33, fitted screw

Brand: EATON - MOELLER | Manufacturer Part Number: S33-1/C/FORMP



Manufacturer	EATON - MOELLER
MPN / Reference	S33-1/C/FORMP
Catalog number	Y7-27446
Category	D-system fuse base
Minimum order	2 Pcs
Document ID	EO-94731736A6
Generated	2026-08-04

Product Overview

Fuse base, 63A, 690 V, DIII/E33, fitted screw

Fuse Base, 1P, 63A, Fixing Screw

Eaton Distribution parts. Fuse base, 63A, 690 V, DIII/E33, fitted screw, C/FORMP

S33 fuse base: accessories for fuses

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Industrial Fuse Bases
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 027446 Model Code S33-1/C/FORMP EAN 4015080274469

Product Length/Depth 80 mm Product Height 79 mm Product Width 45 mm Product Weight 0.148 kg Compliances DIN 49524 (gauge ring system)

VDE 0636 (protective covers)

DIN 49326 (gauge ring system)

DIN 49327 (gauge ring system)

DIN 49510 (RS27 (33)-3/FORMP gauge screw system)

CEE 16 (fuse bases: S27(-1), S33(-1))

VDE 0636 (fuse bases: S27(-1), S33(-1))

RoHS conform Product specifications

Type Special features Can be snap fitted on top-hat rail to IEC/EN 60715 (35 mm)

For gauge ring (gauge screw:/FORMP)

Gauge rings/gauge screws, fuse-links and fuse caps not included as standard

Load carrying capacity of fuse enclosures taking into account the derating factors to IEC/EN 60439 and VDE 0660 Part 500 and Part 504, and the cross-sections of the incoming cable.

Amperage Rating 63 A Number of Poles Single-pole Ambient operating temperature details -5 °C - 25 °C (40 °C, where annual and 24-hour mean value ≥ 35 °C) Voltage rating at AC 660 V AC

690 V AC

Contacts: 690 V AC

Relay contacts: 660 V AC at AC-15

Relay contacts: 690 V AC at AC-15

Rated operational voltage (Ue) - max 690 V Used with Fuse bases 1 pole

Fuse bases Ambient operating temperature - max 55 °C Ambient operating temperature - min -25 °C Current heat loss per contact at rated uninterrupted current I_u 7.5 W Rated uninterrupted current (I_u) 63 A Construction size DIII Mounting position As required Creep...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S33-1/C/FORMP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.