

INDUSTRIAL COMPONENT DATA

S33/C 081460 EATON ELECTRIC Fuse base, 63A, 690 V, DIII/E33, gauge ring

Brand: EATON - MOELLER | Manufacturer Part Number: S33/C



Manufacturer	EATON - MOELLER
MPN / Reference	S33/C
Catalog number	081460
Category	D-system fuse base
Minimum order	1 Pcs
Document ID	EO-9A0F84513F
Generated	2026-08-02

Product Overview

Fuse base, 63A, 690 V, DIII/E33, gauge ring

Fuse Base, 3P, 63A, gauge ring

Fuse base, rated operational current 63A, rated operating voltage 690V, frame size DIII E33, gauge ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Industrial Fuse Bases

Additional Product Information

Fuse base, 63A, 690 V, DIII/E33, gauge ring Fuse base, rated operational current 63A, rated operating voltage 690V, frame size DIII E33, gauge ring Delivery program

Product range Fuse Bases Basic function Fuse bases 3 pole For gauge ring (gauge screw:/FORMP) Can be snap fitted on top-hat rail to IEC/EN 60715 (35 mm) Number of poles 3 pole Rated operational current [Ie] 63 A Rated operational voltage [Ue] 660

690 V AC Fuse cartridge E33, DIII Size Information about equipment supplied Gauge rings/gauge screws, fuse-links and fuse caps not included as standardnotincluded Technical data

General Standards Load carrying capacity of fuse enclosures taking into account the derating factors to IEC/EN 60439 and VDE 0660 Part 500 and Part 504, and the cross-sections of the incoming cable. StandardsFuse bases: S27(-1), S33(-1) VDE 0636

CEE 16 StandardsProtective covers VDE 0636 StandardsGauge ring system DIN 49326 DIN 49327

DIN 49524 StandardsRS27 (33)-3/FORMP gauge screw system DIN 49510 Ambient temperature -5 - +25 (+40, where

annual and 24-hour mean value ? 35) °C Mounting position As required Rated uninterrupted current [Iu] 63 A Contacts
Rated operational voltage [Ue] 690 V AC Creepage and clearance distances VDE 0636 Part 31 Current heat loss per
contact at rated uninterrupted current Iu 7.5 W Terminal capacitiesSolid 2.5 - 16 mm² Terminal capacitiesFlexible with
ferrule 1.5 - 25 mm² Design verification as per IEC/EN 61439
Operating ambient temperature min. -25 °C Operating ambien...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / S33/C with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.