

INDUSTRIAL COMPONENT DATA

FCFDC10DI-2L-SOL 137259 EATON ELECTRIC

Fuse-disconnector with flashing light, 25A DC, 10x38 mm

Brand: EATON - MOELLER | Manufacturer Part Number: FCFDC10DI-2L-SOL



Manufacturer	EATON - MOELLER
MPN / Reference	FCFDC10DI-2L-SOL
Catalog number	137259
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-CDF32A67E4
Generated	2026-08-05

Product Overview

Fuse-disconnector with flashing light, 25A DC, 10x38 mm

String protection of the PV generator, the trip indication shows the blowing of fuse link, 50-400 V flashing, 400-1000 V continuous light, rated operating voltage 1000 VDC, for cylindrical fuse links for photovoltaic application, can be sealed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Fuse-disconnector with flashing light, 25A DC, 10x38 mm String protection of the PV generator, the trip indication shows the blowing of fuse link, 50-400 V flashing, 400-1000 V continuous light, rated operating voltage 1000 VDC, for cylindrical fuse links for photovoltaic application, can be sealed [Delivery program

Product range Fuse disconnecter Application field Residential buildings

Utility buildings

Open areas Description String protection of the PV generator

The trip indication signals the tripped fuse link: 50 - 400 V flashing, 400 - 1000 V continuous

for cylindrical fuse links for photovoltaic application

sealable Connection With flashing function Rated operational voltage [Ue] 1000 V Rated operational current 240 V [Ie] 25 A

Size 10 x 38 Number of poles 2 pole , Technical data

Rated operational voltage [Ue] 1000 V , Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040) Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch

disconnect ( [AKF058013]) Version as main switch No Version as safety switch Yes Max. rated operation voltage Ue AC 0 V Rated permanent current Iu 25 A Rated operation power at AC-23, 400 V 0 kW Conditioned rated short-circuit current Iq 10 kA Rated short-time withstand current Icw 0 kA Suitable for fuses Shape C1-C3 Number of poles 2 With error protection No Type of electr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FCFDC10DI-2L-SOL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.