

INDUSTRIAL COMPONENT DATA

Z-SLS/B-35A 268991 Y7-268991 EATON ELECTRIC Fuse-link with blink application, D02, 35A, 400 V, gL/gG, set co..

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SLS/B-35A



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SLS/B-35A
Catalog number	Y7-268991
Category	D0-system fuse link
Minimum order	1 Pcs
Document ID	EO-3165CE2AF3
Generated	2026-08-04

Product Overview

Fuse-link with blink application, D02, 35A, 400 V, gL/gG, set consists of 3 pcs.

Z-SLS/B-35A

Eaton Distribution parts, Fuse-link with blink application, D02, 35A, 400 V, gL/gG, set consists of 3 pieces

Fuse set with blink operation, frame size D02, rated operational current 32A, color code black, utilization category gG (gL), rated operating voltage 24-60V AC / 24-60V DC, test voltage 5kV, DIN rail mounting, 1 set consists of: 3 fuse bases, 3 current codings, 1 plastic box in the color of the indicator

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 268991 Model Code Z-SLS/B-35A EAN 4015082689919 Product Length/Depth 45 mm Product Height 80 mm Product Width 54 mm Product Weight 0.145 kg Compliances RoHS conform

Product specifications

Type Special features With flashing function

Snap-fit on DIN rail

1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator

Amperage Rating 35 A Frame D02 Used with Z-SLS/CEK

Z-SLS/NEOZ

Z-SLK/NEOZ

Fuse links

Accessory

Fuse material

Fuse set Equipment heat dissipation, current-dependent 2.8 W Utilization category gL/gG (cable protection/equipment protection)

gG (gL) Color Black Ambient operating temperature - max 55 °C Ambient operating temperature - min -25 °C Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Rated operational current for specified heat dissipation (In) 35 A Rated operational voltage (Ue) - max 400 V Rated uninterrupted current (Iu) 35 A Static heat dissipation, non-current-dependent 0 W Test voltage 5 kV Voltage rating at AC 50 - 400 V AC Voltage rating at DC 50 - 250 V DC Functions Accessory Voltage rating 60 V AC - 400 V AC

ETIM for 268991 Circuit breakers and fuses (EC001642)

Feature Name

Feature Value

Construction size (EF002566)

D02

Rated current (EF000227)

35 A

Rated voltage (EF000228)

400 V

Colour code (EF000931)

Black

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SLS/B-35A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.