

INDUSTRIAL COMPONENT DATA

Z-SLS/E-35A 269010 EATON ELECTRIC Fuse-link with blink application, D02, 35A, 400 V, gL/gG

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SLS/E-35A



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SLS/E-35A
Catalog number	269010
Category	D0-system fuse link
Minimum order	1 Pcs
Document ID	EO-941D14CC13
Generated	2026-08-03

Product Overview

Fuse-link with blink application, D02, 35A, 400 V, gL/gG

Fuse link without blink application with D02 fuse, 35A, 400VAC, gL/gG, set consists of 3 pieces

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Fuse link without blink application with D02 fuse, 35A, 400VAC, gL/gG, set consists of 3 pieces Fuse set without blink operation, frame size D02, rated operational current 40A, color code black, utilization category gG (gL), rated operating voltage 400V AC / 220V DC, test voltage 5kV, DIN rail mounting, 1 set consists of: 3 fuse bases, 3 current codings, 1 plastic box in the color of the indicator Delivery program

Product range Fuse material Basic function Accessories Basic function Fuse sets For use with Z-SLS/NEOZ

Z-SLK/NEOZ

Z-SLS/CEK Snap-fit on DIN rail

1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator Rated operating voltage 400 V AC, 220 V DC Technical data

Electrical Rated operational voltage [Ue] Rated operating voltage [Ue] 400 V AC Rated operational voltage [Ue] 220 V

DC Utilization category gG (gL) Test voltage 5 kV Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 35 A Heat dissipation per pole, current-dependent [Pvid] 3.42

W Equipment heat dissipation, current-dependent [Pvid] 3.42 W Static heat dissipation, non-current-dependent [Pvs] 0

W Operating ambient temperature min. -25 °C Operating ambient temperature max. +40 °C Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link () [ACN353011]) Construction size D0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SLS/E-35A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.