

**INDUSTRIAL COMPONENT DATA**

# QSA63N1-00/3 1318027 Y8-1318027 EATON ELECTRIC

## Switch-disconnector-fuse, 3 pole, 63 A, rear mounting, NH00

Brand: EATON - MOELLER | Manufacturer Part Number: QSA63N1-00/3



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | QSA63N1-00/3             |
| Catalog number  | Y8-1318027               |
| Category        | Fuse switch disconnecter |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-C5B6298862            |
| Generated       | 2026-08-03               |

### Product Overview

Switch-disconnector-fuse, 3 pole, 63 A, rear mounting, NH00

QSA63N1-00/3

Eaton QSA Fuse switch-disconnector, 3 pole, rear mounting, 63 A, NH000/NH00, FS1

Fuse switch-disconnector QSA 63N1-00/3, ?frame size 1 suitable for DIN fuse-links (blade contacts type).

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                               |
|--------------|-----------------------------------------------|
| Catalog path | EATON - MOELLER > DUMECO Switch-Disconnectors |
|--------------|-----------------------------------------------|

### Additional Product Information

General specifications

Product Name Eaton QSA Fuse switch-disconnector Catalog Number 1318027 Model Code QSA63N1-00/3 EAN

8711426212077 Product Length/Depth 242 mm Product Height 205 mm Product Width 167 mm Product Weight 1.78 kg

Certifications IEC/EN 60204

RoHS

CE

IEC/EN 60947

IEC/EN 60947-3

VDE 0660 Features &amp; Functions

Features Version as main switch Fitted with: Connectors Functions Optional Stop Function Number of poles Three-pole

General

Accessories Auxiliary contact or neutral conductor fitted by user. Actuator type Without actuator Construction size NH00

Degree of protection IP20, with terminal cover

IP00 Degree of protection (front side) IP00 Mounting method Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product category Rated impulse withstand voltage (Uimp) 6000 V Suitable for DIN fuse-links (blade contacts type)

Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Operating temperature - min -25 °C Operating temperature - max 55 °C

Electrical rating

Rated insulation voltage (Ui) 690 V Rated operating voltage (Ue) at AC - max 690 V Rated operational power at AC-23A, 400 V, 50 Hz 30 kW Rated short-time withstand current (Icw) 0 kA Rated uninterrupted current (Iu) 63 A Uninterrupted current Rated uninterrupted current Iu is specified for max. cross-section. Contacts...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QSA63N1-00/3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.