

INDUSTRIAL COMPONENT DATA

QSA100N1-00/3 1318546 Y8-1318546 EATON ELECTRIC

Switch-disconnector-fuse, 3 pole, 100 A, rear mounting, NH00

Brand: EATON - MOELLER | Manufacturer Part Number: QSA100N1-00/3



Manufacturer	EATON - MOELLER
MPN / Reference	QSA100N1-00/3
Catalog number	Y8-1318546
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-47F8350D0E
Generated	2026-08-05

Product Overview

Switch-disconnector-fuse, 3 pole, 100 A, rear mounting, NH00

QSA100N1-00/3

Eaton QSA Fuse switch-disconnector, 3 pole, rear mounting, 100 A, NH000/NH00

Fuse switch-disconnector QSA100N1-00/3, ?frame size 1 suitable for DIN fuse-links (blade contacts type).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton QSA Fuse switch-disconnector Catalog Number 1318546 Model Code QSA100N1-00/3 EAN 8711426100114 Product Length/Depth 242 mm Product Height 205 mm Product Width 167 mm Product Weight 1.86 kg

Certifications CE

IEC/EN 60204

VDE 0660

RoHS

IEC/EN 60947-3

IEC/EN 60947 Features & Functions

Features Version as main switch Fitted with: Connectors Functions Optional Stop Function Number of poles Three-pole General

Accessories Auxiliary contact or neutral conductor fitted by user. Actuator type Without actuator Construction size NH00

Degree of protection IP00

IP20, with terminal cover Degree of protection (front side) IP00 Mounting method Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product category Rated impulse withstand voltage (Uimp) 6000 V Suitable for DIN fuse-links (blade contacts type)

Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Operating temperature - min -25 °C Operating temperature - max 55 °C

Electrical rating

Rated insulation voltage (Ui) 690 V Rated operating voltage (Ue) at AC - max 690 V Rated operational power at AC-23A, 400 V, 50 Hz 55 kW Rated short-time withstand current (Icw) 0 kA Rated uninterrupted current (Iu) 100 A Uninterrupted current Rated uninterrupted current Iu is specified for max. cross-section. Contac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QSA100N1-00/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.