

INDUSTRIAL COMPONENT DATA

QSA200N-2/3 1318547 Y8-1318547 EATON ELECTRIC

Switch-disconnector-fuse, 3 pole, 200 A, rear mounting, NH1/NH2

Brand: EATON - MOELLER | Manufacturer Part Number: QSA200N-2/3



Manufacturer	EATON - MOELLER
MPN / Reference	QSA200N-2/3
Catalog number	Y8-1318547
Category	Fuse switch disconnector
Minimum order	1 Pcs
Document ID	EO-E8D95AF2A5
Generated	2026-08-06

Product Overview

Switch-disconnector-fuse, 3 pole, 200 A, rear mounting, NH1/NH2

QSA200N-2/3

Eaton QSA Fuse switch-disconnector, 3 pole, rear mounting, 200 A, NH1/NH2

Fuse switch-disconnector QSA200N-2/3, ?frame size 2 suitable for DIN fuse-links (blade contacts type).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton QSA Fuse switch-disconnector Catalog Number 1318547 Model Code QSA200N-2/3 EAN

8711426131613 Product Length/Depth 170 mm Product Height 210 mm Product Width 250 mm Product Weight 4.05 kg

Certifications CE

IEC/EN 60947-3

IEC/EN 60204

RoHS

IEC/EN 60947

VDE 0660 Features & Functions

Features Version as main switch Fitted with: Connectors Functions Optional Stop Function Number of poles Three-pole

General

Accessories Auxiliary contact or neutral conductor fitted by user. Actuator type Without actuator Construction size NH1, NH2 Degree of protection IP00

IP20, with terminal cover Degree of protection (front side) IP00 Mounting method Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product category Rated impulse withstand voltage (Uimp) 6000 V Suitable for Ground mounting

DIN fuse-links (blade contacts type) Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Operating temperature - min -25 °C Operating temperature - max 55 °C

Electrical rating

Rated insulation voltage (Ui) 690 V Rated operating voltage (Ue) at AC - max 690 V Rated operational power at AC-23A, 400 V, 50 Hz 110 kW Rated short-time withstand current (Icw) 0 kA Rated uninterrupted current (Iu) 200 A Uninterrupted current Rated uninterrupted current Iu is specified for max. cross-section. Con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QSA200N-2/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.