

## INDUSTRIAL COMPONENT DATA

# QSA315N-2/3 1318548 Y8-1318548 EATON ELECTRIC Switch-disconnector-fuse, 3 pole, 315 A, rear mounting, NH1/NH2

Brand: EATON - MOELLER | Manufacturer Part Number: QSA315N-2/3



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | QSA315N-2/3              |
| Catalog number  | Y8-1318548               |
| Category        | Fuse switch disconnector |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-F7864E4436            |
| Generated       | 2026-08-05               |

## Product Overview

Switch-disconnector-fuse, 3 pole, 315 A, rear mounting, NH1/NH2

QSA315N-2/3

Eaton QSA Fuse switch-disconnector, 3 pole, rear mounting, 315 A, NH1/NH2

Fuse switch-disconnector QSA315N-2/3, ?frame size 2 suitable for DIN fuse-links (blade contacts type).

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                               |
|--------------|-----------------------------------------------|
| Catalog path | EATON - MOELLER > DUMECO Switch-Disconnectors |
|--------------|-----------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton QSA Fuse switch-disconnector Catalog Number 1318548 Model Code QSA315N-2/3 EAN

8711426142268 Product Length/Depth 338 mm Product Height 235 mm Product Width 183 mm Product Weight 5.31 kg

Certifications RoHS

IEC/EN 60947

IEC/EN 60947-3

CE

VDE 0660

IEC/EN 60204 Features & Functions

Features Version as main switch Fitted with: Connectors Functions Optional Stop Function Number of poles Three-pole

## General

Accessories Auxiliary contact or neutral conductor fitted by user. Actuator type Without actuator Construction size NH1, NH2 Degree of protection IP00

IP20, with terminal cover Degree of protection (front side) IP00 Mounting method Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product category Rated impulse withstand voltage (Uimp) 6000 V Suitable for Ground mounting

DIN fuse-links (blade contacts type) Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Operating temperature - min -25 °C Operating temperature - max 55 °C

## Electrical rating

Rated insulation voltage (Ui) 690 V Rated operating voltage (Ue) at AC - max 690 V Rated operational power at AC-23A, 400 V, 50 Hz 184 kW Rated short-time withstand current (Icw) 0 kA Rated uninterrupted current (Iu) 315 A Uninterrupted current Rated uninterrupted current Iu is specified for max. cross-section. Con...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QSA315N-2/3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

## GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.