

INDUSTRIAL COMPONENT DATA

QSA400-3/3 1318549 Y8-1318549 EATON ELECTRIC

Switch-disconnector-fuse, 3 pole, 400 A, rear mounting, NH3

Brand: EATON - MOELLER | Manufacturer Part Number: QSA400-3/3



Manufacturer	EATON - MOELLER
MPN / Reference	QSA400-3/3
Catalog number	Y8-1318549
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-E15DA1CFF7
Generated	2026-08-05

Product Overview

Switch-disconnector-fuse, 3 pole, 400 A, rear mounting, NH3

QSA400-3/3

Eaton QSA Fuse switch-disconnector, 3 pole, rear mounting, 400 A, NH3

Fuse switch-disconnector QSA400-3/3, ?frame size 3 suitable for DIN fuse-links (blade contacts type)., ithe 750 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton QSA Fuse switch-disconnector Catalog Number 1318549 Model Code QSA400-3/3 EAN

8711426745377 Product Length/Depth 280 mm Product Height 240 mm Product Width 355 mm Product Weight 13.85 kg

Certifications CE

IEC/EN 60947

VDE 0660

IEC/EN 60204

IEC/EN 60947-3

RoHS Features & Functions

Features Version as main switch Fitted with: Connectors Functions Optional Stop Function Number of poles Three-pole

General

Accessories Auxiliary contact or neutral conductor fitted by user. Actuator type Without actuator Construction size NH3

Degree of protection IP20, with terminal cover

IP00 Degree of protection (front side) IP00 Mounting method Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product category Rated impulse withstand voltage (Uimp) 6000 V Suitable for Ground mounting

DIN fuse-links (blade contacts type) Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Operating temperature - min -25 °C Operating temperature - max 55 °C

Electrical rating

Rated insulation voltage (Ui) 690 V Rated operating voltage (Ue) at AC - max 690 V Rated operational power at AC-23A, 400 V, 50 Hz 220 kW Rated short-time withstand current (Icw) 0 kA Rated uninterrupted current (Iu) 400 A Uninterrupted current Rated uninterrupted current Iu is specified for max. cross-section. Contacts...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QSA400-3/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.