

INDUSTRIAL COMPONENT DATA

FWA-2500AHI EATON ELECTRIC Fuse-link, high speed, 2500 A, AC 130 V, 48 x 76 mm, aR, UL, with indicator

Brand: EATON - MOELLER | Manufacturer Part Number: FWA-2500AHI



Manufacturer	EATON - MOELLER
MPN / Reference	FWA-2500AHI
Catalog number	FWA2500AHI
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-D2CBE29B83
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 2500 A, AC 130 V, 48 x 76 mm, aR, UL, with indicator
2500Amp 130V FUSE (INDICATED) - Fuse-link, high speed, 2500 A, AC 130 V, 48 x 76 mm, aR, UL, with indicator
Fuse, Fuse-link, high speed, 2500 A, AC 130 V, 48 x 76 mm, aR, UL, with indicator, cylindrical with flush end, UL 248-13, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann fuses
--------------	----------------------------------

Additional Product Information

Fuse-link, high speed, 2500 A, AC 130 V, 48 x 76 mm, aR, UL, with indicator
Fuse, Fuse-link, high speed, 2500 A, AC 130 V, 48 x 76 mm, aR, UL, with indicator, cylindrical with flush end, UL 248-13, Breaking Capacity 200 kA
Delivery program
Product range
Fuse
Basic function
Fuse-link
Field of application
high speed
Rated current [I]
2500 A
Rated voltage
AC 130 V
Size
48 x 76 mm
Utilization category
aR
Status indicator
with indicator
Breaking Capacity
200 kA
Standard/Approval
UL
Shape
cylindrical with flush end
Standards/Regulations
UL 248-13
Technical data
ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015])
Construction size
Other
Rated current
2500 A
Rated voltage
130 V
Voltage type
AC
Rated switching capacity
200 kA
Utilization category
aR (accompanied semiconductor protection)
Type of fuse status indicator
Other
Insulated metal gripping lugs (IMGL)
No
ETIM for FWA-2500AHI
Circuit breakers and fuses (EC004556)
Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

2500 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

0.2 kA

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

130 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FWA-2500AHI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.