

INDUSTRIAL COMPONENT DATA

FWC-30A10F EATON ELECTRIC Emergency-stop pushbutton, D 38mm, key unlocking, closure according to data

Brand: EATON - MOELLER | Manufacturer Part Number: FWC-30A10F



Manufacturer	EATON - MOELLER
MPN / Reference	FWC-30A10F
Catalog number	FWC30A10F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-FA2A0BC720
Generated	2026-08-06

Product Overview

30Amp 600Vac 10 X 38mm FERRULE FUSE

Eaton Bussmann series FWC high speed cylindrical fuse, 500 Vac/dc (35-800A only), 30A, 200 kAIC Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

Fuse, Fuse-link, high speed, 30 A, AC 600 V, 10 x 38 mm, aR, UL, cylindrical, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248, Breaking Capacity 200 kA, Optional accessories fuse-holder CHM1DU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWC-30A10F EAN 5027590499385
UPC 051712370851 Product Length/Depth 44 mm Product Height 23 mm Product Width 54 mm Product Weight 9.4 g

Compliances CE Marked

RoHS Compliant Certifications CSA Certified

UL Recognized Electrical data

Amperage Rating 30 A Voltage rating 700 V Voltage type AC/DC Interrupt rating 200 kAIC Vac Class Class aR Pre arc (I2T) 95 Clearing (I2T) 600 at 600 V Watt losses 7.5 W Product specification

Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Fuse indicator Other Fuse size 10 x 38 mm Compatible microswitch

Accessories

ETIM for FWC-30A10F Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

10x38 mm

Voltage type (EF000187)

AC/DC

Rated current (EF000227)

30 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

Other

Release characteristic (EF000889)

Other

Power loss at rated current (EF012389)

7.5 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FWC-30A10F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.