

INDUSTRIAL COMPONENT DATA

FWP-25A14FI EATON ELECTRIC cartridge fuse, ultra rapid, 25a, AC 700 V 14 x 51 mm, aR, UL, with the front

Brand: EATON - MOELLER | Manufacturer Part Number: FWP-25A14FI



Manufacturer	EATON - MOELLER
MPN / Reference	FWP-25A14FI
Catalog number	FWP25A14FI
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-364300E70B
Generated	2026-08-06

Product Overview

25A 690V 14X51 INDICATED 14.3 X 50.8MM

Eaton Bussmann series FWP high speed fuse, 690 Vac (IEC), 700 Vac (UL), 600 Vdc (UL), 25A, 200 kAIC at 700 Vac, 50 kAIC at 600 Vdc, With Indicator, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic Fuse, Fuse-link, high speed, 25 A, AC 700 V, 14 x 51 mm, aR, UL, with striker, cylindrical, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 200 kA, Optional accessories fuse-holder CH141B

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWP-25A14FI EAN 5027590500470
UPC 051712510769 Product Length/Depth 52 mm Product Height 15 mm Product Width 15 mm Product Weight 20.4 g
Compliances CE Marked

RoHS Compliant Certifications UL Recognized

CSA Certified Product specifications

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage
Rating 25 A Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse indicator Top fuse
status indicator Release characteristic Other Utilization category aR (accompanied semiconductor protection) Voltage type
AC/DC Fuse size 14 x 51 mm Class Class aR Clearing (I2T) 320 Watt losses 7 W Fuse shape Cylindrical Pre arc (I2T) 49

Used with Finger safe holders/blocks and striker Color White Interrupt rating 200 kAIC Fitted with: Striker Connection
Ferrule end x ferrule end Construction size 14 mm x 51 mm Material Ceramic Packaging type Standard Quantity 10 Voltage
rating 700 V Fuse type FWP-A14FI

ETIM for FWP-25A14FI Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

14x51 mm

Voltage type (EF000187)

AC/DC

Rated current (EF000227)

25 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

Top fuse status indicator

Release characteristic (EF000889)

Other

Power loss at...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FWP-25A14FI with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.