

INDUSTRIAL COMPONENT DATA

FWX-15A14F EATON ELECTRIC Fuse-link, high speed, 15 A, AC 250 V, DC 250 V, 14 x 51 mm, aR, UL

Brand: EATON - MOELLER | Manufacturer Part Number: FWX-15A14F



Manufacturer	EATON - MOELLER
MPN / Reference	FWX-15A14F
Catalog number	FWX15A14F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-F794B349D1
Generated	2026-08-06

Product Overview

250V 15AMP S/COND FERRULE 14.3 X 50.8MM

Eaton Bussmann series FWX high speed fuse, 15A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

Fuse, Fuse-link, high speed, 15 A, AC 250 V, DC 250 V, 14 x 51 mm, aR, UL, cylindrical, Ferrule, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248-13, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWX-15A14F EAN 5027590501347

UPC 051712795579 Product Length/Depth 55 mm Product Height 32 mm Product Width 73 mm Product Weight 22.4 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized Product specifications

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage

Rating 1500 A Accessories Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse

indicator Other Release characteristic Other Utilization category aR (accompanied semiconductor protection) Voltage type

AC Fuse size 14 x 51 mm Class Class aR Clearing (I2T) 83 at 250 V Watt losses 3.8 W Fuse shape Cylindrical Pre arc

(I2T) 14 Interrupt rating 200 kAIC Connection Ferrule end x ferrule end Construction size 14 mm x 51 mm Material Ceramic

Packaging type Standard Voltage rating 700 V Fuse type FWX-A14F

ETIM for FWX-15A14F Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

14x51 mm

Voltage type (EF000187)

AC

Rated current (EF000227)

1500 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

Other

Release characteristic (EF000889)

Other

Power loss at rated current (EF012389)

3.8 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FWX-15A14F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.