

INDUSTRIAL COMPONENT DATA

FWX-25A14F EATON ELECTRIC Fuse-link, low voltage, 1 A, AC 250 V, UL Class K5, 14.3 x 50.8, UL

Brand: EATON - MOELLER | Manufacturer Part Number: FWX-25A14F



Manufacturer	EATON - MOELLER
MPN / Reference	FWX-25A14F
Catalog number	FWX25A14F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-16CAAA94F7
Generated	2026-08-06

Product Overview

25AMP 250V AC FERRULE 14.3 X 50.8MM

Eaton Bussmann series FWX high speed fuse, 600V, 25A, 200 kAIC Vac, 50 kAIC at 250 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

Fuse, Fuse-link, high speed, 25 A, AC 250 V, DC 250 V, 14 x 51 mm, aR, UL, cylindrical, Ferrule, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248-13, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWX-25A14F EAN 5027590501378

UPC 051712795593 Product Length/Depth 55 mm Product Height 32 mm Product Width 73 mm Product Weight 21.2 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized Electrical data

Amperage Rating 2500 A Voltage rating 700 V Voltage type AC Interrupt rating 200 kAIC Class Class aR Pre arc (I2T) 58

Clearing (I2T) 300 at 250 V Watt losses 5.3 W Product specification

Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Fuse indicator Other Fuse size 14 x 51 mm Compatible microswitch

Accessories

ETIM for FWX-25A14F Circuit breakers and fuses (EC002704)

Feature Name
Feature Value
Model (EF000010)
Ceramic fuse
Size (EF000088)
14x51 mm
Voltage type (EF000187)
AC
Rated current (EF000227)
2500 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Type of fuse status indicator (EF004473)
Other
Release characteristic (EF000889)
Other
Power loss at rated current (EF012389)
5.3 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FWX-25A14F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.