

INDUSTRIAL COMPONENT DATA

XN-GW-CANOPEN 140050 EATON ELECTRIC CANopen Gateway 85 50 225163

Brand: EATON - MOELLER | Manufacturer Part Number: XN-GW-CANOPEN



Manufacturer	EATON - MOELLER
MPN / Reference	XN-GW-CANOPEN
Catalog number	140050
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-4AC6D8C8C8
Generated	2026-08-05

Product Overview

CANopen Gateway 85 50 225163

Gateway CANopen

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Delivery programme Function Gateways XI/ON

Connection technique Tension spring connection

Function XN gateway without integrated supply

Short Description supports up to 74 disc-type modules (XN)

1 x 9-pole SUB-D socket

1 x 9-pin SUB-D plug connector

Address setting with two hexadecimal rotary coding switch

Address range: 1 - 127 (dec.)

Field bus connection CANopen®

Terminal capacity (field bus/supply voltage) 2 x spring-cage terminal strips for direct wiring

Service interface PS/2 socket

Data transfer rate 1000 Kbit/s

800 Kbit/s

500 Kbit/s

250 Kbit/s

125 kbit/s

50 Kbit/s

20 Kbit/s

10 Kbit/s

Instructions The supply module XN-BR-24VDC-D must be mounted immediately next to the gateway to provide the supply for the gateway.

Information about equipment supplied The delivery package for all gateways includes: 2 x end bracket XN-WEW-32/2-SW, 1 x end plate XN-ABPL

Technical data General

Standards EN 61000-6-2

EN 61000-6-4

EN 61131-2

Potential isolation Yes, through optocoupler

Ambient temperature °C 0 - +55

Storage ? °C -25 - +85

Relative humidity 5 - 95 % (indoor), Level RH-2, no condensation (for storage at 45°C)

Harmful gases ppm SO₂: 10 (rel. humidity < 75%, no condensation)

H₂S: 1.0 (rel. humidity < 75 %,no condensation)

Vibration according to IEC/EN 60068-2-6

Mechanical shock resistance g according to IEC 60068-2-27

Continuous shock resistance (IEC/EN 60068-2-29) According to IEC 60068-2-29

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32

Degree...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-GW-CANOPEN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.