

INDUSTRIAL COMPONENT DATA

EASY223-SWIRE 106950 EATON ELECTRIC Gateway CANopen-easyNet/SmartWire

Brand: EATON - MOELLER | Manufacturer Part Number: EASY223-SWIRE



Manufacturer	EATON - MOELLER
MPN / Reference	EASY223-SWIRE
Catalog number	106950
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-D81A31501E
Generated	2026-08-01

Product Overview

Gateway CANopen-easyNet/SmartWire

SmartWire-DT gateway for connection to the field bus and for supply of the SmartWire-DT card and switchgears.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > EASY programmable relays and MFD displays
--------------	---

Additional Product Information

Delivery programme Description Gateway for connecting up to 16 SmartWire modules to easyNet or CANopen®

Noteseasy-NET operating mode

CANopen® operating mode

In easy-NET mode the gateway acts as a station on easy-NET and the SmartWire master at the same time. Up to 8 stations on the easy-NET can be intelligently connected with each other.

CANopen® mode allows communication between SmartWire modules and controllers with CANopen® interface such as EC4-200 or XC100/200. In addition to standard fieldbus modules such as remote I/O systems or visualisation devices, this allows a number of switchgear devices can be networked directly with the PLC. Up to 126 stations can be connected to a CANopen® network, depending on the performance level of the CANopen® fieldbus master.

General

Standards EN 55011, EN 55022, IEC/EN 61000-4, IEC/EN 60068-2-27, EN 50325

Dimensions (W x H x D) mm 35.5 x 90 x 58 (2 PE)

Weight kg 0.15

Mounting Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)

Terminal capacitiesSolid mm² 0.34 - 1.5 (AWG 22 - 16)Flexible with ferrule mm² 0.34 - 1.5 (AWG 22 - 16)

Standard screwdriver mm 3.5 x 0.8

Max. tightening torque Nm 0.6

Climatic environmental conditions

Operating ambient temperature °C -25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2

Condensation Take appropriate measures to prevent condensation

Storage °C - 25 - 70

Relative humidity, non-condensing (IEC/EN 60068-2-30) % 5 - 95

Air pressure (operation)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY223-SWIRE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.